



UNIQUE-Q TECH INDIA PVT LTD
108 & 109, "YAJAMAN THIMMAIAH ENCLAVE"
Madanayakanahalli, Survey No.27, Dasanupura Hobli,
Ph: +91-80-2991 9449, +91-23432 32111, +91-93421 22193.
Email: pmr@unique-techindia.com, sales@unique-techindia.com,
www.unique-techindia.com



Univon Air All in One Domestic Hot Water Heat Pump Specifications

w.e.f: 01-10-2023

| Model | Univon Air 200L | Univon Air 250L | Univon Air 300L |
|---|---|--|---|
|  |  |  |  |
| Rated heating Capacity | kW | 2.5 | 2.5 |
| Electric heater* | kW | 2 | 2 |
| Rated power input** | W | 600 (+2000*) | 600 (+2000*) |
| Rated current** | A | 2.9 (+ 8.6*) | 2.9 (+ 8.6*) |
| COP** | | 4.16 | 4.16 |
| Energy class*** (ERP) | | A | A |
| Power supply | V/Ph/Hz | 220-240/1/50 | |
| Max outlet water temperature (without using E-heater) | °C | 60 | |
| Compressor | | GMCC(Toshiba) PJ125 | |
| Refrigerant | | R134a | |
| Inner tank material | | Steel Enamel tank. | |
| Heat pump heat exchanger coil | | Copper External coil | |
| Solar thermal connection | | Internal coil MS | |
| Expansion valve | | Electronic expansion valve included | |
| Rated water yield | L/H | 61 | 61 |
| Max. water operating pressure | Mpa | 1.0 | 1.0 |
| Rated water pressure | Mpa | 0.6 | 0.6 |
| Set point relief valve | Mpa | 0.7 | 0.7 |
| Sound pressure level | dB (A) | 48 | 48 |
| Net weight | kg | 88 | 95 |
| Net size (WxHxD) | mm | Φ570x1785 | Φ570x2070 |
| Package size (WxHxD) | mm | 700x700x2250 | 700x700x2250 |

**Testing conditions: Ambient temperature 28°C, water temperature from 20°C to 60°C.

***Testing conditions: Based on standard ERP, XL cycle: Ambient temperature 30°C/25°C, water temperature from 20°C to 60°C)

Notes:

1. The above specifications are subject to change without prior notice for product improvement. For final parameters, please refer to the nameplate on the machine.
2. Warranty: 1 year for the whole unit.

For Unique-Q Tech India Pvt. Ltd.



(Prashanth M R)

Cell, WhatsApp, WeChat : +91-94482 79449

THANK YOU FOR YOUR BUSINESS!